## (19) World Intellectual Property **Organization**

International Bureau



# 

(43) International Publication Date 3 March 2005 (03.03.2005)

## (10) International Publication Number WO 2005/019333 A1

(51) International Patent Classification7: 23/06, C08J 5/18

C08L 23/08,

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/GB2004/003483

(22) International Filing Date: 12 August 2004 (12.08.2004)

(25) Filing Language:

**English** 

(26) Publication Language:

**English** 

(30) Priority Data:

0319467.7

19 August 2003 (19.08.2003) GB

(71) Applicant (for all designated States except US): BP CHEMICALS LIMITED [GB/GB]; Chertsey Road, Sunbury on Thames, Middlesex TW16 7BP (GB).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): CHAI, Choon, Kooi [MY/FR]; 7 Avenue Van Gogh, Domaine de Calas, F-13480 Cabries (FR).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,

### **Declarations under Rule 4.17:**

GW, ML, MR, NE, SN, TD, TG).

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,

(LDPE) polymer having a density from 0.914 to 0.928 g cm<sup>-3</sup> wherein the sum of (a) and (b) is 100 %. The copolymers of component (a) are typically prepared by use of metallocene catalysts. The blends exhibit advantageous melt elastic modulus in the range 30 to 200 Pa. The blends are particularly suitable for extrusion coating applications.